



R18

HEAVY DUTY STRAIGHT LINE RIPSAW
"Cuts from below"



FEATURES

- Extra heavy main frame throughout with large support table
- 6" minimum length with this type of saw the blade is cutting downwards ie. Forcing the Blade onto the chain hence max. stability and safety are realized.
- Better chip clearance for shavings on deep cutting
- Glue joint range – 12" to 10 Ft.
- Depth of cut 4.7" (120mm) max.
- Split chain – double track with HRC60 Rockwell Hardened Guideways
- 26" (660mm) saw to column
- 8 press rolls hold material firmly on the track
- 15 HP direct drive
- 2 HP feed motor
- Feed speed 33 to 180 FPM variable
- Automatic chain and track oiler
- 41" length of chain above table
- Saw arbor height adjustable
- Max. 18" Blade \varnothing x 2" Bore \varnothing saw Arbor with 14mm pin at 65mm centers
- Saw arbor brake Included
- Anti-kickback fingers top and bottom
- Dust collection outlets:
 - Top 5.75" 700 CFM
 - Bottom 5" 550 CFM
- Table dimensions – 82" x 40" x 33.5" high
- Net weight - 4400 lbs
- Stock machine electrics 460/3/60 to UL/CSA Standards (Other voltages available on request)

OPTIONS AVAILABLE

*** Option is included on our stock machines*

- 20HP Main Drive motor - Direct drive **
- 3HP Feed Motor **
- Outside Side Safety Guard, rear pressure device **
- Bottom row of anti-kickback fingers pneumatically activated **
- Pneumatic Locking Floating Fence System max range 24" - shift speed up to 24"/sec. **
- 20 Mw Laser Unit In Line, 110 volt c/w universal mounting bracket