DIEHL SL-30 STRAIGHT LINE RIP SAW



Diehl's Most Affordable Rip Saw with the same guaranteed glue line accuracy of our larger saws.

All this coupled with Diehl's legendary quality and durability.



EHL SL-30 AIGHT LINE RIP SAW

Over 85 years of rip saw manufacturing experience has been put to use developing the SL series of straight line rip saws. The SL-30 features a 10 HP or an optional 15 Hp arbor motor. Diehl's proven chain/race, spindle/arbor and

pressure roll system make up the foundation for this saw that produces the industry's most accurate glue line cut, guaranteed. The Diehl SL-30 is the rip saw that you can depend on for continuous quality performance.



Voltages Available

Arbor Motor	10 HP (7.5 Kw), 15 HP (11.2 Kw) optional
Feed Motor	1 1/2 HP (1.12 Kw)
Feed Speed	Fixed 60 FPM (18.3 mpm)
Stock Capacities Minimum Thickness	1/8" (3 mm)
Maximum Thickness w/14" (355 mm) blade w/16" (406 mm) blade	1.5" (38 mm) 2.55" (64 mm)
Minimum Length	*15" (381 mm)
Saw Blade Arbor Bore	2" (50.8 mm)
Throat Capacity	19" (482 mm)
Arbor RPM Belt Driven	3450
Accurate Glue Line Cut (either straight or hollow)	up to 5' (1.5 m)

J	380, 3 phase, 50 cycle w/110 control circuit
Spindle Brake	automatic
Vacuum	1 - 6" (152 mm) and 1 - 3" (76 mm) opening 1250 CFM (35 cmm) required
Upper Anti-Kickback Fingers w/Cam Controlled Height	

208/240/480/575, 3 phase, 60 cycle

Lower Anti-Kickback Fingers in Table

65" (1651 mm) L x 53" (1346 mm) W x 56" Dimensions (1423 mm) H

net 2,750 lbs. (1250 kg) Weight crated 2,960 lbs. (1345 kg)

crated for export shipment 3,275 lbs. (1485 kg)

nominal 34" (864 mm) Worktable Height



^{*9&}quot; (229 mm) w/ optional equipment