WP2510 Planer



WP2510 Planer

FEATURES

Solid steel helical insert head with four-sided carbide insert tooling, no adjustment required after changing knives — Reduced sound levels when running and cutting

Built with digital readout and simple PC controller to make quick and easy table height set ups

Segmented serrated infeed roll with segmented chip breakers for planning multiple height stock — Each segment has independent yield of 1/4"

3" diameter infeed and outfeed rollers are supported by four large, sealed, needle bearings for long life

"Quick-Set" micro-adjustable lever easily raises and lowers table rollers from 0" to 0.050" at a touch

Frame machined from heavy cast iron and extra wide side panels with gibs, offers rigid bed support and accurate alignment

Solid pressure bar has wide foot for long wear and can be adjusted on both ends for precise feeding

Feed selector allows you to quickly change feed rate from low to high

Large 32-3/16" x 26" precision-ground table contains two adjustable table rollers for smooth feeding of uneven stock

Massive gear box maintains a positive feed by using a large chain drive to power the infeed and outfeed rollers

Gear box incorporates automatic chain tensioners

Dust hood features an excellent dust collection system with built-in 5" dust chute

Model	WP2510
Stock Number	1791303
Maximum Cutting Width (in.)	25
Maximum Cutting Thickness (in.)	9
Full Width Cutting Depth (in): 10-3/8" <w<25"< td=""><td>1/8</td></w<25"<>	1/8
Maximum Cutting Depth (in.): W≤10-3/8"	1/4
Minimum Planning Length (in.)	10
Number of Knives, Helical Head	168 Four-sided inserts
Segmented Infeed Roller Diameter (in.)	3
Steel Outfeed Roller Diameter (in.)	3
Cutter Head Speed (RPM)	5000
Cuts Per Minute	30,000
Cutter Head Diameter (in.)	3-3/8
Feed Rate (FPM)	30-25-20
Dust Chute Diameter (in.)	5
Table Area (D x W/in.)	32-3/16 x 26
Main Drive Motor	15HP, 3Ph, 230/460V, Prewired 230V
Table Hoist Motor	1/2HP, 3Ph
Overall Dimensions (L x W x H/in.)	52 x 36 x 59
Net Weight (lbs.)	1725
Shipping Weight (lbs.)	1850

