3760 WIDE BELT SANDERS

From big table tops to face frame stock there is nothing our Safety Speed Wide Belt Sander can't make nice and smooth! Greg Fedeczko, Edwards, CO

Safety Speed Wide Belt Sanders solve the most tedious challenge facing woodworkers: Improve flat panel sanding results while saving time.

Our American Made <u>3760 Wide Belt Sander</u> improves your finishing time, decreases hand sanding and increases productivity.

These machines are configurable to

meet your needs and are workhorses that will likely outlive you.





Features

- 4.25" Diameter Contact Roller
- Rubber-covered pinch rollers (2)
- 3/4" diameter jackscrews (4)
- Photo electric belt tracking.
- Platen 2.5" and removable.
- Emergency stops (5).
- Pneumatic belt tensioning.
- 6" internal dust chute.
- Conveyor Motor (3/4 Hp)
- 3 year warranty.

Optional Equipment

- Digital Readout (DRO)
- Hour Meter
- 460 Voltage Configuration
- · Additional Sanding Belts

3760 Wide Belt Sander			
Motor Configurations			220 Volt 208 / 230 Volt
Max. Working Length	Unlimited		
Min. Working Length	12"/ 305mm		
Max. Working Width	36"/915mm		
Max. Working Thickness	7.25"/184mm		
Min. Working Thickness	1/8", 3mm		
Machine Dimensions	50.5"D x 63"H x 47"W		
Vacuum Requirement	1000 CFM		
Conveyor Speed	0-18 FPM		
Durometer of Contact Roller	60		
Sanding Belt Size	37" x 60"		
Shipping Weight	1362lbs/618KG		